

Powered by



RG0632LT1 6V 3.2Ah

This is a general purpose battery up to 5 years in standby service or more than 260 cycles at 100% discharge in cycle service. It is rechargeable, highly efficient, leak proof and maintenance free.

► Specification

Cells Per Unit	3
Voltage Per Unit	6
Capacity	3.2Ah @ 20hr-rate to 1.75V per cell @25°C (77°F)
Weight	Approx. 0.63 kg (1.386 lbs)
Maximum Discharge Current	48A(5sec)
Internal Resistance	Approx. 35 mΩ
Operating Temperature Range	Discharge: -15°C~50°C (5°F~122°F) Charge: -15°C~40°C (5°F~104°F) Storage: -15°C~40°C (5°F~104°F)
Nominal Operating Temperature Range	25°C±3°C (77°F±5°F)
Float Charging Voltage	6.75 to 6.9 VDC/unit Average at 25°C (77°F)
Recommended Maximum Charging Current Limit	0.96A
Equalization and Cycle Service	7.2 to 7.5 VDC/unit Average at 25°C (77°F)
Self Discharge	This battery can be stored for more than 6 months at 25°C (77°F). Please charge batteries before using. For higher temperatures the time interval will be shorter.
Terminal	F1-Faston Tab187
Container Material	ABS(UL 94-HB) & Flammability resistance of (UL 94-V0) can be available upon request.




► Dimensions :

Unit: mm

Overall Height (H)	Container height (h)	Length (L)	Width (W)
68±1.5	62±1.5	134±1.5	34±1

unit : mm



Constant Current Discharge Characteristics Unit:A (25°C, 77°F)


F.V/Time	5min	15min	30min	1h	3h	5h	10h	20h
1.60V	10.0	5.9	3.37	1.93	0.84	0.566	0.302	0.162
1.67V	9.8	5.7	3.35	1.92	0.84	0.564	0.302	0.162
1.7V	9.7	5.6	3.32	1.89	0.83	0.559	0.300	0.161
1.75V	9.2	5.4	3.26	1.85	0.82	0.551	0.298	0.160
1.8V	8.3	5.0	3.13	1.76	0.79	0.535	0.292	0.157
1.85V	6.4	4.2	2.88	1.61	0.72	0.496	0.275	0.150

Constant Power Discharge Characteristics Unit:W (25°C, 77°F)


F.V/Time	5min	15min	30min	1h	3h	5h	10h	20h
1.60V	18.9	11.3	6.51	3.67	1.66	1.083	0.594	0.321
1.67V	18.0	10.7	6.49	3.65	1.65	1.083	0.594	0.321
1.7V	17.4	10.4	6.43	3.61	1.63	1.075	0.590	0.320
1.75V	15.9	9.6	6.33	3.56	1.61	1.060	0.584	0.318
1.8V	13.7	8.5	6.10	3.45	1.55	1.026	0.573	0.312
1.85V	10.7	7.2	5.61	3.20	1.43	0.968	0.544	0.299

Ratings presented herein are subject to revision without notice.


Trickle(or Float)Design Life




Capacity Retention Characteristic




Battery Voltage and Charge Time for Standby Use




Cycle Service Life



Battery Voltage and Charge Time for Cycle Use



Terminal Voltage (V) and Discharge Time



Charging Procedures

Application	Charge Voltage(V/Cell)			Max.Charge Current
	Temperature	Set Point	Allowable Range	
Cycle Use	25°C (77°F)	2.45	2.40~2.50	0.3C
Standby	25°C (77°F)	2.275	2.25~2.30	

Discharge Current VS. Discharge Voltage

Final Discharge Voltage V/Cell	1.75	1.70	1.65	1.60
Discharge Current(A)	0.2C>(A)	0.2C<(A)<0.5C	0.5C<(A)<1.0C	(A)>1.0C

Effect of temperature on capacity (20HR)

Temperature	Dependency of Capacity (20HR)
40 °C	102%
25 °C	100%
0 °C	85%
-15 °C	65%

Self-discharge Characteristics

Storage time	Preservation rate
3 Months	91%
6 Months	82%
12 Months	64%