

Powered by



RG1280T2 12V 8Ah

RG1280T2 is a general purpose battery up to 5 years in standby service or more than 260 cycles at 100% discharge in cycle service. This battery is rechargeable, highly efficient, leak proof and maintenance free.

► Specification


Cells Per Unit	6
Voltage Per Unit	12
Capacity	8Ah @ 20hr-rate to 1.75V per cell @25°C (77°F)
Weight	Approx. 2.35 kg(5.17 lbs)
Maximum Discharge Current	112.5A(5sec)
Internal Resistance	Approx. 17 mΩ
Operating Temperature Range	Discharge: -15°C~50°C (5°F~122°F) Charge: -15°C~40°C (5°F~104°F) Storage: -15°C~40°C (5°F~104°F)
Nominal Operating Temperature Range	25°C±3°C (77°F±5°F)
Float Charging Voltage	13.5 to 13.8 VDC/unit Average at 25°C (77°F)
Recommended Maximum Charging Current Limit	2.25A
Equalization and Cycle Service	14.4 to 14.8 VDC/unit Average at 25°C (77°F)
Self Discharge	Raion batteries can be stored for more than 6 months at 25°C (77°F). Please charge batteries before using. For higher temperatures the time interval will be shorter.
Terminal	F2-Faston Tab 250
Container Material	ABS(UL 94-HB) & Flammability resistance of (UL 94-V0) can be available upon request.



► Dimensions :

Unit: mm

Overall Height (H)	Container height (h)	Length (L)	Width (W)
100±1.5	94±1.5	151±2	65±1.5



Constant Current Discharge Characteristics Unit:A (25°C, 77°F)


F.V/Time	5min	15min	30min	1h	3h	5h	10h	20h
1.60V	27.9	13.2	7.88	4.51	2.00	1.37	0.746	0.399
1.67V	26.1	12.6	7.70	4.38	1.98	1.35	0.743	0.395
1.7V	24.6	12.1	7.55	4.30	1.96	1.32	0.735	0.391
1.75V	23.2	11.2	7.35	4.20	1.94	1.31	0.728	0.387
1.8V	20.6	10.7	6.94	4.05	1.88	1.25	0.709	0.375
1.85V	18.6	9.8	6.30	3.93	1.78	1.18	0.683	0.364

Constant Power Discharge Characteristics Unit:W (25°C, 77°F)


F.V/Time	5min	15min	30min	1h	3h	5h	10h	20h
1.60V	51.2	25.0	15.2	8.88	3.94	2.70	1.468	0.790
1.67V	48.6	24.3	15.1	8.70	3.97	2.67	1.473	0.788
1.7V	45.6	23.1	14.7	8.51	3.90	2.63	1.457	0.780
1.75V	43.0	21.4	14.3	8.31	3.87	2.60	1.441	0.776
1.8V	38.2	20.5	13.5	8.00	3.75	2.49	1.404	0.749
1.85V	34.8	18.9	12.4	7.84	3.58	2.37	1.365	0.733

Ratings presented herein are subject to revision without notice.


Trickle(or Float)Design Life




Capacity Retention Characteristic




Battery Voltage and Charge Time for Standby Use




Cycle Service Life



Battery Voltage and Charge Time for Cycle Use



Terminal Voltage (V) and Discharge Time



Charging Procedures

Application	Charge Voltage(V/Cell)			Max.Charge Current
	Temperature	Set Point	Allowable Range	
Cycle Use	25°C(77°F)	2.45	2.40~2.50	0.3C
Standby	25°C(77°F)	2.275	2.25~2.30	

Discharge Current VS. Discharge Voltage

Final Discharge Voltage V/Cell	1.75	1.70	1.60	1.30
Discharge Current(A)	0.2C>(A)	0.2C<(A)<0.5C	0.5C<(A)<1.0C	(A)>1.0C

Effect of temperature on capacity (20HR)

Temperature	Dependency of Capacity (20HR)
40 °C	102%
25 °C	100%
0 °C	85%
-15 °C	65%

Self-discharge Characteristics

Storage time	Preservation rate
3 Months	91%
6 Months	82%
12 Months	64%